

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
5 December 2002 (05.12.2002)

PCT

(10) International Publication Number
WO 02/096536 A1

- (51) International Patent Classification?: B01D 33/04, 33/056
- (21) International Application Number: PCT/ZA02/00095
- (22) International Filing Date: 31 May 2002 (31.05.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2001/4486 31 May 2001 (31.05.2001) ZA
- (71) Applicants and
(72) Inventors: BUISMAN, Reindert [NL/ZA]; 2 Lark Crescent, Greenhills, 1759 Randfontein, Gauteng (ZA).
ALTMANN, Werner, Hartmut [AT/CH]; Töbelmuehle, CH-Bischoffzell (CH).
- (74) Agent: LE ROUX, Marius; D M Kisch Inc, P.O. Box 781218, Sandton 2146 (ZA).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEHYDRATING PRESS FOR A SLUDGE



(57) Abstract: A dehydration apparatus (10) for a sludge comprises an endless first metal screen (14) having a first section (14.1) and a second section (14.2). Material to be dehydrated is introduced onto section (14.1) at inlet (18). A liquid collection region (70) is located between the first and second sections. The liquid collection region comprises a liquid suction chamber connected to a compressed air driven venturi (78) for generating suction in the chamber. The apparatus further comprises a press having a compression region (22) formed by converging sections (14.1) and (16.1). Vibrators (28.1), hot air introducing boxes and liquid suction boxes (30.1) adjacent the compression region aid in the dewatering process. Dehydrated cakes are delivered between rollers (13) and (17).

Best Available Copy

WO 02/096536 A1

DEHYDRATING PRESS FOR A SLUDGE

TECHNICAL FIELD

THIS invention relates to solid and liquid separating apparatus and
5 more particularly to dehydration filters, and filter presses.

Separating apparatus in the form of filter presses for removing liquids
from a sludge are known in the art. The known filter presses suffer
from one or the other disadvantage. For example, some filter presses
10 comprise cooperating moving endless screens, made of a synthetic
material, to press the liquid from the sludge. Each of the screens is
fed about a plurality of rollers and idlers and has positive and negative
bends therein. These opposite bends limit the operational life of the
screens. Furthermore, the screens are often hydrophilic, which
15 reduces the drainage through the screens. Still furthermore, the
known screens, in use, become stretched and strands are flattened
out, which reduce the open areas of the screens and hence the
drainage and dehydrating capability thereof. Still furthermore, many of
the known apparatus cannot accommodate heating stages and/or
20 coarser solid particles.

OBJECT OF THE PRESENT INVENTION

Accordingly it is an object of the present invention to provide apparatus with which the applicant believes the aforementioned disadvantages may at least be alleviated.

5

SUMMARY OF THE INVENTION

According to the invention there is provided filter apparatus comprising:

- an endless first metal screen having a first section and a second section;
- a liquid collection region located between the first and second sections;
- the liquid collection region comprising a liquid suction chamber connected to a compressed air driven device for generating suction in the chamber.

10

15

The metal is preferably stainless steel.

The screen may comprise a plurality of parallel weft elements in the form of stainless steel rods and a plurality of parallel warp elements in the form of stranded stainless steel cables.

20

The screen may in use move along a closed trajectory about longitudinally spaced first and second end rollers, so that the first section extends linearly between the first roller and the second roller and the second section is a return run.

5

The second roller may be driven by suitable drive means such as an electric motor, to cause the screen to move.

10

An inlet for matter to be filtered may be provided onto the first section in a region thereof towards the first roller.

15

The inlet may comprise an arrangement for distributing the matter evenly onto the first section. The arrangement may comprise a first plate slanting in a first direction and a second plate slanting in a transverse direction and defining a transversely extending opening onto the first section between the first plate and the second plate. The first and second plates may be housed in an inlet box and the box may comprise a trailing blade extending transversely to the first section.

20

The liquid collection region may comprise a sump defining the liquid suction chamber and the sump may comprise a top wall defining a plurality of holes to admit liquid.

5 Sidewalls of the sump may slant towards an outlet and the compressed air driven device may be provided downstream from the outlet.

10 The device may comprise one of a venturi and a compressed air ventilator.

The apparatus may further comprise a press for the matter.

15 The press is preferably located downstream from said liquid collection region and towards the second roller.

The press preferably comprises a second endless screen providing a compression zone between the second screen and the first section of the first screen.

20

The second screen is preferably made of metal such as stainless steel and is mounted in use to move along a closed trajectory about first

and second longitudinally spaced rollers for the second screen, so that a first section extends linearly between the first and second rollers for the second screen and a return section extends between the second roller and the first roller.

5

The compression zone is preferably provided between the first section of the first screen and the first section of the second screen which converge towards one another in a direction towards the second rollers.

10

The first section of the first screen and the first section of the second screen may be guided in the compression zone by transversely extending roller pairs. A first roller of each pair may support the first section of the first screen in the compression zone and is preferably longitudinally offset relative to another roller in the pair.

15

At least one liquid collection region comprising a liquid suction chamber connected to a compressed air driven device for generating suction in the chamber is provided adjacent the compression zone.

20

A vibration generating system may also be provided adjacent the compression zone. The system may comprise a housing, a moveable

member located in the housing, an inlet for compressed air into the housing and an outlet for the air from the housing into the zone. In other embodiments the means for generating vibrations may be electrically driven.

5

A reflector for vibrations may be provided on another side of the compression zone.

10

The compressed air is preferably heated to a temperature higher than 100°C.

Also included within the scope of the invention is a method of filtering a liquid from a mixture thereof with solids, the method comprising the steps of

15

- utilizing a first metal screen to transmit the liquid and to stop the solids; and
- utilizing suction generated by a compressed air driven device, to facilitate transmission of the liquid.

20

The mixture may also be fed through a compression zone formed between the first metal screen and a second metal screen.

BRIEF DESCRIPTION OF THE ACCOMPANYING DIAGRAMS

The invention will now further be described, by way of example only, with reference to the accompanying diagrams wherein:

- 5 figure 1 is a diagrammatic side view of apparatus according to the invention;
- figure 2 is a longitudinal section through the apparatus in figure 1;
- figure 3 is a diagrammatic perspective view of a mixture feed box forming part of the apparatus;
- 10 figure 4 is a diagrammatic perspective view of a screen and suction box forming part of the apparatus; and
- figure 5 is a schematic diagram of a compression zone of the apparatus.

DESCRIPTION OF A PREFERRED EMBODIMENT OF THE INVENTION

- 15 A filter press for a sludge (such as sewage), slurry, paper pulp, coal, iron ore and the like is generally designated by the numeral 10 in figures 1 and 2.

- 20 The filter 10 comprises an elongate frame 12 supporting in a bottom region thereof a first or bottom endless screen 14 extending about longitudinally spaced first and second end rollers 11 and 13. The frame further supports in a top region thereof a second or upper

endless screen 16 extending about longitudinally spaced first and second end rollers 15 and 17.

5 Adjacent each of first end rollers 11 and 15 there are provided pneumatically operated screen tensioning mechanisms 19 and 21. Furthermore, screen 14 also extends past pneumatically operable screen tracking mechanism 23, and screen 16 extends past a similar screen tracking mechanism 25. The tensioning and tracking mechanisms cooperate with one another to accommodate the screens.

10 Each screen is made of stainless steel and in use, is driven to follow a closed trajectory. Screen 14 follows closed trajectory A in a clockwise direction and screen 16 follows closed trajectory B in an anti-clockwise direction. Screen 14 has a linear first section or top run 14.1 extending from roller 11 to roller 13 and a return run 14.2. Screen 16 has a linear first section or bottom run 16.1 extending from roller 15 to roller 17 and a return run 16.2. As is shown in figures 1 and 2, the screens are bent in one direction only, in that rollers and idlers about which the screens are bent are all located on the inside of the respective trajectories. The screens are driven by suitable electric motors (not shown) driving second end rollers 13 and 17 respectively. Each screen comprises a plurality of parallel weft members 114.1 in

the form of stainless steel rods and a plurality of parallel warp elements 114.2 in the form of stranded stainless steel cables.

5 As shown in figure 1, towards one end 12.1 of frame 12, first screen 14 extends beyond screen 16. An inlet onto screen 14 for matter to be dehydrated, is provided at 18. The inlet is shown in more detail in figure 3 and comprises a box 50 having a floor 52 of a synthetic plastic material defining holes 54. An inlet duct 56 communicates with the box and transversely extending plates 58, 60 in the box
10 define a transversely extending slot 62 between them. A flexible blade 64 of rubber or the like distributes the material evenly onto section 14.1 of screen 14.

15 As shown in figure 2, between first section or top run 14.1 of screen 14 and second section or return run 14.2 there is provided a suction box 70, shown in more detail in figure 4.

The sidewalls 71 and bottom 73 of box 70 are made of stainless steel. A top 72 is made of a synthetic plastic material and defines a plurality
20 of holes 74. The sidewalls and bottom slope towards an outlet 76. Apart from the holes 74, the box is substantially airtight. As shown

in figure 2, the top 72 overlaps at least partially with floor 52 of inlet box 50.

The outlet 76 is connected to a compressed air driven device such as a venturi 78 or ventilator (not shown) to generate suction inside the box 70.

The compressed air is provided via duct 80.

As shown in figure 5, in region 20 of frame 12, screen 14 and screen 16 converge towards one another in the direction of other end 12.2 of the frame, to define a wedge shaped compression zone 22, between bottom run 16.1 of upper screen 16 and top run 14.1 of bottom screen 14.

As best shown in figures 1 and 2, transversely extending elongate rollers 24.1 to 24.5 guiding the bottom run of upper screen 16 in region 20 are slightly off-set in a longitudinal direction of the frame from corresponding rollers 26.1 to 26.5 supporting the top run of bottom screen 14. In a preferred embodiment and as shown in figure 5, first or upper roller 24.1 of a roller pair 24.1, 26.1 leads the other roller 26.1 of the pair.

As shown in figures 1 and 2, above section 16.1 of screen 16 adjacent region 20 and between adjacent pairs of off-set rollers, such as pair 24.2, 26.2 and pair 24.3, 26.3 there are provided low frequency vibration generating arrangements 28.1 and 28.2. Also
5 between adjacent roller pairs, but below section 14.1 of screen 14 there are provided low pressure or suction arrangements 30.1 and 30.2, substantially similar to the arrangement 70 hereinbefore described.

10 Referring to figure 5, each vibration generating arrangement comprises a compressed air vibrator 31 and a box 32. Each vibrator 31 is connected via a conduit system 34 to a source 36 of hot (between 100°C and 150°C) and compressed air. The hot air is utilized to agitate a ball (not shown) in a housing of the vibrator 31. The air
15 moves through the vibrator and holes in a floor of box 32 to be ejected into the wedge shaped compression zone 22 via the holes. Below top run 14.1 of mesh 14 and opposite boxes 32, there may be provided reflectors (not shown) to reflect upwardly and back towards wedge shaped zone 22 incident vibrations generated by the arrangements
20 28.1 to 28.3.

The suction arrangements 30.1 to 30.3 are connected to a venturi system 38 to produce low pressure or liquid suction regions below top run 14.1 of screen 14 and preferably immediately downstream of each pair of off-set rollers. The venturi system is also connected to the source 36 of compressed air by duct 40, to utilize the compressed air, to generate the low pressure or suction regions. The sumps of arrangements 30.1 to 30.3 may be connected via a manifold 42 to system 38. A drain for the water filtered out is shown at 44.

In use, sludge to be dehydrated is received on section 14.1 of screen 14 of the apparatus in region 18. Initial dehydration is performed by the screen 14.1 and liquid suction box 70. The sludge is then fed by screen 14 into the wedge shaped zone 22. In the wedge shaped zone, the sludge is sandwiched between the converging bottom screen 14 and upper screen 16. Liquid is now pressed out of the sludge by the cooperating screens. The dewatering is aided by the vibrations generated adjacent zone 22. Furthermore, the hot air ejected into the zone 22 further assists in the dewatering action and the suction arrangements 30.1 to 30.3 still further assists in removing liquid from the sludge. Dehydrated cakes are recovered at 38 at end 12.2 of frame 12.

CLAIMS**1. Filter apparatus comprising:**

- an endless first metal screen having a first section and a second section;
- a liquid collection region located between the first and second sections;
- the liquid collection region comprising a liquid suction chamber connected to a compressed air driven device for generating suction in the chamber.

2. Apparatus as claimed in claim 1 wherein the metal is stainless steel.**3. Apparatus as claimed in claim 1 or claim 2 wherein the screen comprises a plurality of parallel weft elements in the form of stainless steel rods and a plurality of parallel warp elements in the form of stranded stainless steel cables.****4. Apparatus as claimed in any one of claims 1 to 3 wherein the screen in use moves along a closed trajectory about longitudinally spaced first and second end rollers, so that the**

first section extends linearly from the first roller to the second roller and the second section is a return run.

5 5. Apparatus as claimed in claim 4 wherein the second roller is driven to cause the screen to move.

 6. Apparatus as claimed in claim 4 or claim 5 wherein an inlet for matter to be filtered is provided onto the first section in a region thereof towards the first roller.

10

 7. Apparatus as claimed in claim 6 wherein the inlet comprises an arrangement for distributing the matter evenly onto the first section.

15

 8. Apparatus as claimed in claim 7 wherein the arrangement comprises a first plate slanting in a first direction and a second plate slanting in a transverse direction and defining a transversely extending opening onto the first section between the first plate and the second plate.

20

9. Apparatus as claimed in claim 8 wherein the first and second plates are housed in an inlet box and wherein the box comprises a trailing blade extending transversely to the first section.
- 5 10. Apparatus as claimed in any one of claims 1 to 9 wherein the liquid collection region comprises a sump defining the liquid suction chamber, the sump comprising a top wall defining a plurality of holes to admit liquid.
- 10 11. Apparatus as claimed in claim 10 wherein sidewalls of the sump slant towards an outlet.
12. Apparatus as claimed in claim 11 wherein the compressed air driven device is provided downstream from the outlet.
- 15 13. Apparatus as claimed in any one of the preceding claims wherein the device comprises one of a venturi and a compressed air ventilator.
- 20 14. Apparatus as claimed in any one of claims 1 to 13 comprising a press.

15. Apparatus as claimed in claim 14 wherein the press is located downstream from said liquid collection region and towards the second roller.
- 5 16. Apparatus as claimed in claim 14 or claim 15 wherein the press comprises a second endless screen providing a compression zone between the second screen and the first screen.
- 10 17. Apparatus as claimed in claim 16 wherein the second screen is made of stainless steel and is mounted in use to move along a closed trajectory about longitudinally spaced first and second rollers for the second screen, so that a first section extends linearly from the first roller to the second roller for the second screen and a return section extends from the second roller to the first roller.
- 15 18. Apparatus as claimed in claim 17 wherein the compression zone is provided between the first section of the first screen and the first section of the second screen which converge towards one another in a direction towards the second rollers.
- 20

19. Apparatus as claimed in claim 18 wherein the first section of the first screen and the first section of the second screen are guided in the compression zone by transversely extending roller pairs.

5

20. Apparatus as claimed in claim 19 wherein a first roller of each pair supports the first section of the first screen in the compression zone and is longitudinally offset relative to another roller in the pair guiding the first section of the second screen.

10

21. Apparatus as claimed in any one of claims 16 to 20 wherein at least one liquid collection region comprising a liquid suction chamber connected to a compressed air driven device for generating suction in the chamber is provided adjacent the compression zone.

15

22. Apparatus as claimed in any one of claims 16 to 21 wherein a vibration generating system is provided adjacent the compression zone, the system comprising a housing, a moveable member located in the housing, an inlet for compressed air into the housing and an outlet for the air from the housing into the zone.

20

23. Apparatus as claimed in claim 22 comprising a reflector for vibrations located on another side of the compression zone.

5 24. Apparatus as claimed in claim 22 or claim 23 wherein the compressed air is heated to a temperature higher than 100°C.

25. A method of filtering a liquid from a mixture thereof with solids, the method comprising the steps of

- utilizing a first metal screen to transmit the liquid and to
- 10 stop the solids; and
- utilizing suction generated by a compressed air driven device, to facilitate transmission of the liquid.

26. A method as claimed in claim 25 wherein the mixture is fed

15 through a compression zone formed between the first metal screen and a second metal screen.




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/ZA 02/00095

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B01D33/04 B01D33/056

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 90 13347 A (SVENSK INDUSTRIALJOE AB) 15 November 1990 (1990-11-15) page 4, line 8 - page 7, line 4; figures 1-5	1-7, 14, 25
X	GB 2 166 660 A (GREEN BAY PACKAGING INC) 14 May 1986 (1986-05-14) the whole document	1, 2, 4-7, 14, 16-20, 25, 26
A	US 3 979 296 A (BASTGEN WENDELL) 7 September 1976 (1976-09-07) column 2, line 10 - line 42; figures 1, 2	1-26
A	EP 0 798 333 A (DAIKIN IND LTD) 1 October 1997 (1997-10-01) abstract; figures 1-3	1-26

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search

19 July 2002

Date of mailing of the international search report

26/07/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Sembritzki, T

INTERNATIONAL SEARCH REPORT

International Application No
PCT/ZA 02/00095

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 458 413 A (PANNEVIS BV) 27 November 1991 (1991-11-27) abstract; figures 1-7	1-26
A	EP 0 523 821 A (MANNESMANN AG) 20 January 1993 (1993-01-20) column 2, line 19 - line 37; figure 1	1-26

INTERNATIONAL SEARCH REPORT
Information on patent family members

Int. l. Application No
PCT/ZA 02/00095

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9013347	A	15-11-1990	SE 465856 B	11-11-1991
			AU 5555490 A	29-11-1990
			SE 8901709 A	13-11-1990
			WO 9013347 A1	15-11-1990
GB 2166660	A	14-05-1986	AU 4940785 A	15-05-1986
			DE 3539233 A1	07-05-1986
			FI 854299 A	08-05-1986
			IT 1182655 B	05-10-1987
			JP 61115699 A	03-06-1986
			SE 8505124 A	08-05-1986
			ZA 8508448 A	24-09-1986
US 3979296	A	07-09-1976	DE 2127974 A1	14-12-1972
			AR 202451 A1	13-06-1975
			AT 319972 B	27-01-1975
			BE 784310 A1	02-10-1972
			CA 984218 A1	24-02-1976
			CH 539446 A	31-07-1973
			DK 138931 B	20-11-1978
			ES 402596 A1	16-03-1975
			FR 2140435 A1	19-01-1973
			GB 1395050 A	21-05-1975
			IE 36456 B1	10-11-1976
			IT 956021 B	10-10-1973
			NL 7207523 A	07-12-1972
			SE 408374 B	11-06-1979
			US 3800952 A	02-04-1974
			ZA 7203154 A	26-09-1973
EP 0798333	A	01-10-1997	EP 0798333 A1	01-10-1997
			RU 2149164 C1	20-05-2000
			CN 1141640 A ,B	29-01-1997
			WO 9523178 A1	31-08-1995
EP 0458413	A	27-11-1991	NL 9001170 A	16-12-1991
			AT 148363 T	15-02-1997
			AU 632692 B2	07-01-1993
			AU 7717291 A	21-11-1991
			CA 2042833 A1	22-11-1991
			CN 1023769 B	16-02-1994
			CN 1057402 A	01-01-1992
			CS 9101474 A3	15-01-1992
			DE 69124419 D1	13-03-1997
			DE 69124419 T2	24-07-1997
			EP 0458413 A1	27-11-1991
			ES 2097786 T3	16-04-1997
			FI 912440 A ,B,	22-11-1991
			IL 98192 A	28-11-1994
			JP 3187069 B2	11-07-2001
			JP 4227807 A	17-08-1992
			KR 203458 B1	15-06-1999
			NO 911944 A ,B,	22-11-1991
			RU 2035965 C1	27-05-1995
			US 5133883 A	28-07-1992
EP 0523821	A	20-01-1993	DE 4123746 A1	21-01-1993
			EP 0523821 A2	20-01-1993

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.